

PNEUMATIC BREAKERS

TEX140 - TEX280

15.5 - 31.5 KG



Applications:

- Light to medium sized breakers for service jobs and general demolition in soft and medium hard materials

Features:

- Solid Body concept
- Noise reduction
- HAPSTTM Hand and Arm Protection System (PE series)
- SOFSTARTTM two-step trigger
- Rotating air inlet swivel
- Integrated lubricator

| | TEX140PS | | TEX150PE | | TEX180PS | | TEX190PE | | TEX220PS | | | TEX230PE | | | TEX270PS | | TEX280PE | |
|---|----------|--------|----------|--------|----------|--------|----------|--------|----------|--------|--------|----------|--------|--------|----------|--------|----------|--------|
| Vibro-reduced | NO | NO | YES | YES | NO | NO | YES | YES | NO | NO | NO | YES | YES | YES | NO | NO | YES | YES |
| Weight kg | 15.5 | 15.5 | 19 | 19 | 19 | 19.5 | 22.5 | 23 | 22 | 23.5 | 23.5 | 25.5 | 25.5 | 27 | 28 | 28 | 31.5 | 31.5 |
| Length mm | 590 | 590 | 590 | 590 | 595 | 645 | 595 | 645 | 625 | 670 | 670 | 625 | 625 | 670 | 690 | 690 | 690 | 690 |
| Air consumption l/s | 25 | 25 | 25 | 25 | 26 | 26 | 26 | 26 | 30 | 30 | 30 | 30 | 30 | 30 | 32 | 32 | 32 | 32 |
| Impact rate bpm | 1530 | 1530 | 1530 | 1530 | 1500 | 1500 | 1500 | 1500 | 1320 | 1320 | 1320 | 1320 | 1320 | 1320 | 1230 | 1230 | 1230 | 1230 |
| Vibration level 3 axis m/s ² | 15.2 | 15.2 | 4.5 | 4.5 | 14.5 | 14.5 | 3.7 | 3.7 | 12.8 | 12.8 | 12.8 | 4.2 | 4.2 | 4.2 | 14.9 | 14.9 | 4.8 | 4.8 |
| Sound power level Lw, dB(A) | 104 | 104 | 104 | 104 | 104 | 104 | 104 | 104 | 104 | 106 | 106 | 104 | 104 | 106 | 105 | 105 | 105 | 105 |
| Shank size Hex mm | 22x82.5 | 25x108 | 22x82.5 | 25x108 | 25x108 | 28x160 | 25x108 | 28x160 | 25x108 | 28x160 | 32x160 | 25x108 | 28x160 | 32x160 | 28x160 | 32x160 | 28x160 | 32x160 |

| Available shank sizes | 22 x 82.5 | 25 x 108 | 28 x 160 | 32 x 160 |
|-----------------------|------------|------------|------------|------------|
| TEX140PS Part number | 8461022330 | 8461022332 | | |
| TEX150PE Part number | 8461022331 | 8461022333 | | |
| TEX180PS Part number | | 8461022430 | 8461022432 | |
| TEX190PE Part number | | 8461022431 | 8461022433 | |
| TEX220PS Part number | | 8461022530 | 8461022532 | 8461022533 |
| TEX230PE Part number | | 8461022531 | 8461022534 | 8461022535 |
| TEX270PS Part number | | | 8461022630 | 8461022631 |
| TEX280PE Part number | | | 8461022632 | 8461022633 |



PNEUMATIC BREAKERS

TEX P60S - TEX P90S

TEX32 - TEX40

33 - 43 KG



Applications:

- Heavy duty demolition breakers for use in medium and hard materials such as asphalt and reinforced concrete

Features:

- Solid Body concept
- Noise reduction
- HAPS™ Hand and Arm Protection System (PE series)
- Rotating air inlet swivel
- Integrated lubricator

| Pneumatic Breakers | TEX P60S | | TEX32PS | | TEX33PE | | TEX39PS | | TEX40PE | | TEX P90S | |
|---|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|
| Vibro-reduced | NO | NO | NO | NO | YES | YES | NO | NO | YES | YES | NO | NO |
| Weight kg | 33 | 33 | 34 | 34 | 37 | 37 | 39 | 39 | 42 | 42 | 43 | 43 |
| Length mm | 690 | 690 | 745 | 745 | 745 | 745 | 750 | 750 | 750 | 750 | 710 | 710 |
| Air consumption l/s | 36 | 36 | 34 | 34 | 34 | 34 | 40 | 40 | 40 | 40 | 40 | 40 |
| Impact rate bpm | 1500 | 1500 | 1200 | 1200 | 1200 | 1200 | 1110 | 1110 | 1110 | 1110 | 1260 | 1260 |
| Vibration level 3 axis m/s ² | 16.8 | 16.8 | 13.7 | 13.7 | 5.7 | 5.7 | 14.3 | 14.3 | 4.2 | 4.2 | 15.3 | 15.3 |
| Sound power level Lw, dB(A) | 109 | 109 | 111 | 111 | 111 | 111 | 111 | 111 | 111 | 111 | 111 | 111 |
| Shank size Hex mm | 28X160 | 32X160 | 28X160 | 32X160 | 28X160 | 32X160 | 28X160 | 32X160 | 28X160 | 32X160 | 28X160 | 32X160 |
| Part No | 8461022722 | 8461022723 | 8461022703 | 8461022705 | 8461022701 | 8461022700 | 8461022803 | 8461022801 | 8461022805 | 8461022804 | 8461022822 | 8461022823 |

Ph: 1300 WALTAN (1300 925 826) Fax: (08) 8297 0500 Email: sales@waltan.com.au