

ROTARY TUBE CLEANERS

Electric & Pneumatic



	RAM-PRO	RAM-PRO-XL-A	RAM4-A-50	RAM-5DC	RAM6-A-50	AWT-100	AWT-100X
Part Number	9980100315	9980100320	9980100280	9980100330	9980100335	9980100230	9980100235
Application	Smooth Bore & Enhanced Tube	Smooth Bore & Enhanced Tube	Smooth Bore & Enhanced Tube	Smooth Bore Tube	Smooth Bore & Enhanced Tube	Smooth Bore Tube/Pipes/Hoses	Smooth Bore Tube/Pipes/Hoses
Tube Size Range (mm)	6.4 to 25.4 ID	6.4 to 25.4 ID	6.4 to 25.5 ID	6.4 to 25.6 ID	6.4 to 25.6 ID	6.4 and Up	6.4 and Up
Input Power	0.4Kw, 4.5A, 230V, 50Hz	0.4Kw, 10A, 230V, 50/60Hz	0.4Kw, 4.5A, 230V, 50Hz	0.7Kw, 6A, 230V, 50Hz	1.1Kw, 7.5A, 230V, 50Hz	Up to 1.1Kw	Up to 3Kw
Air Requirement	*	*	*	*	*	4.1-6.9 Bar @ 25-119 M ³ /H	4.1-6.9 Bar @ 144-221 M ³ /H
Shaft Speed (rpm)	862.5	Adjustable 0-900	862.5	Adjustable 200 - 862.5	Adjustable 200 - 800	Adjustable 500 - 3000	Adjustable 500 - 3001
Shaft Feed	Manual	Manual	Manual	1/4"-1" manual, 7/16"-1" Power	Manual	Manual	Manual
Water Requirement	Minimum 2.1 Bar @ 7.6 l/m	Minimum 2.1 Bar @ 7.6 l/m	Minimum 2.1 Bar @ 7.6 l/m	Minimum 2.1 Bar @ 7.6 l/m	Minimum 1.7 Bar @ 8.3 l/m	Minimum 2.1 Bar @ 7.6 l/m	Minimum 2.1 Bar @ 11.4 l/m
Special Features	Reversible Shaft Rotation	Reversible Shaft Rotation	Reversible Shaft Rotation (Opt)	Reversible Shaft Rotation (Opt)	Reversible Shaft Rotation	Air Powered	Air Powered
	Water Flush	Water Flush with On Board Chemical Dispenser	Water Flush	Water Flush	Water Flush	Water Flush	Water Flush
	Chain Drive	Roll Cage with Integrated Wheels and Handles	*	Mechanical Feed upto 0.9m/sec	Chemical Insertion	Variable Speed	Variable Speed
	Roll Cage	Direct Drive	*	Mechanical Feed Force 23Kg	Up to 34 Bar Water Flush	Optional Vacuum Attachment	Optional Vacuum Attachment
Dimensions (mm) Nom.	400H x 230W x 510D	500H x 400W x 660D	940H x 510W x 430D	940H x 510W x 430D	1170H x 610W x 460D	260H x 150W x 480D	940H x 510W x 430D
Weight (Kg) Dry	16	25	22	34	47	13	24

Ph: 1300 WALTAN (1300 925 826) Fax: (08) 8297 0500 Email: sales@waltan.com.au