

PNEUMATIC STANDARD HAMMERS TEX03-TEX12

4.0 - 12.5KG

Applications depending on weight class:

- Light duty chipping and scaling work
- Renovation and conversion work
- Demolition

Features:

- Noise reduction
- SOFSTART™ two-step trigger
- Air cushioned piston



Standard Hammer	TEX03PS ²	TEX05P ^{1,2}	TEX09 PSKL	TEX09 PS/PSR	TEX10 PSKL	TEX10 PS/PSR	TEX12 PSKL/ PSRKL	TEX12 PS/PSR
Weight kg	4.0	5.5	12	10	10.5	10	12.5	10.5
Length mm	300	380	500	500	500	520	545	550
Air consumption l/s	6.9	9.5	18.5	18.5	17	17	21.3	21.3
Impact rate bpm	4080	2760	1800	1800	1350	1350	1600	1600
Vibration level 3 axis m/s ²	16.5	13	16.1	16.1	22.4	22.4	15.4	15.4
Sound power level Lw,dB(A)	105	104	105	103	103	102	105	105
Tool retainer	cap	cap	kick latch	cap	kick latch	cap	kick latch	cap
Shank size Hex mm	19x50	19x50	22x82.5	22x82.5	22x82.5	22x82.5	22x82.5	22x82.5
Part No (hex shank)	8461020801	8461021900	8461021105	8461021102	8461021132	8461021130	8461021112	8461021113
Kit Part No	8461020802	8461021902
Shank size Round mm	.	17.3x60	.	25x75	.	25x75	25x75	25x75
Part No (round shank)	.	8461021903	.	8461021104	.	8461021131	8461021115	8461021114

KL: kick latch
PS: silenced
PSR: round shank

¹⁾ also available with combined hex/round shank - **Part no 8461021901**

²⁾ also available in carrying case as complete set (hex shank only)

Important: full details are available in the Product Safety & Operating Instructions - contact us for details

PNEUMATIC VIBRO-REDUCED HAMMERS TEX05-TEX12

6.5 - 12KG

Applications depending on weight class:

- Light duty chipping and scaling work
- Renovation and conversion work
- Demolition
- Kiln stripping

Features:

- Full canopy vibro-reduction (TEX05,09,12)
- Noise reduction
- SOFSTART™ two-step trigger
- HAPST™ Hand and Arm Protection System
- Air cushioned piston (TEX05,09,12)
- Easy handling and positioning



Vibro-reduced Hammer	TEX05PE	TEX07PE	TEX07PE FSH ¹	TEX09PE/PER ¹	TEX12PE/PER ¹
Weight kg	6.5	8.5	9	10.5	12
Length mm	450	525	525	560	590
Air consumption l/s	10	17	17	17	20
Impact rate bpm	2640	1770	1770	1800	1620
Vibration level 3 axis m/s ²	2.4	12.4	10.5	4.2	4
Sound power level Lw,dB(A)	105	104	104	105	105
Tool retainer	cap	cap	cap	latch	latch
Shank size Hex mm	19x50	19x50	19x50	22x82.5	22x82.5
Part No (hex shank)	8461021910	8461020920	8461020921	8461021135	8461021138
Shank size Round mm	.	.	.	25x70	25x70
Part No (round shank)	.	.	.	8461021136	8461021139

PE: silenced, vibro reduced

PER: silenced, vibro reduced, round shank

FSH: front side handle

¹: front side handle included

Important: full details are available in the Product Safety & Operating Instructions - contact us for details