

HOIST ANCHOR 2S 415V ER003SD 0.25T X 3M



Features

- 60% Duty cycle for single speed units, 40/20% for dual speed
- IP55 rated enclosure
- IP65 rated pendant control
- Fan cooled motor allows for extended use
- Upper/lower limit switches to avoid damage to the hoist and chain
- Friction clutch to prevent overloading
- Ergonomically designed pendant control complete with emergency stop feature
- Lightweight aluminium die cast body
- Thermal protector to prevent overheating
- Counter/hour meter to assist maintenance procedures
- Dual speed models are controlled by an inverter system allowing for customer nominated speed settings (within a range), allowing smoother movement between speeds, reducing load swing and damage to lifting parts
- Nickel plated load chain to resist corrosion and lengthen chain life
- Available in 250kg to 20T configurations
- Also available are Motorised, Geared and Push type trolleys to suit each hoist

Applications

- Used in Chemical, Manufacturing, Mining, Food, Major Utilities, Service, Agriculture and process industries

Specifications:

Brand PWB Anchor

Capacity kg 250

Capacity T 0.25

Hoisting Speed m/min 10.8/1.8

Lift m 3

Minimum Order Quantity 1

Order Quantity Multiple 1

Power kW 0.56

Standard Pack Quantity 1

Type 3-Phase/2-Speed

Voltage 415